

wedi Sanbath *Cube/Wave* | bathtub

- Ready-to-install bathtub
- For direct tiling
- Incl. drainage



General product description

wedi Sanbath bathtub is a pre-fabricated bathtub for individual tiling. Special orders are also possible.

Applications

For private and commercial use indoors with a direct load from tap and cleaning water.

Product properties

- Waterproof
- Heat insulating
- Stable and lightweight

Surface requirements

The floor must have a sufficient load capacity and must be even.

Processing

Information on processing and surface requirements can be found in the wedi "Building materials" brochure and the fitting instructions (see www.wedi.de).

Technical data sheet

Technical properties – Rigid foam

Extruded polystyrene rigid foam core	XPS
Long-term compressive strength (50 years) \leq 2% compression EN 1606	0.08 N/mm ²
Compressive resistance at 10% compression EN 826	0.25 N/mm ²
Thermal conductivity EN 13164	0.033 W/mK
Bulk density EN 1602	32 kg/m ³
Temperature limits	-50°C / +75°C
Fire behaviour/Building material class DIN 4102	B1
Fire behaviour EN 13501-1	E

Technical properties – Drain and overflow fittings

Sealed, built-in drain and overflow fittings

Overflow capacity	up to 0.6 l/s; 36 l/min
Drain capacity	up to 1.0 l/s; 60 l/min
Water level	355 mm

Packing

- Bathtub element
- Special orders possible
- Drain and overflow fittings with outlet supports DN 40/50
- Bowden cable with rotary button
- Substructure element
- Fundo Fino exclusive cover
- Fundo Fino elegant frame, stainless steel

Storage

The wedi Sanbath bathtub should be stored such that it is protected from external mechanical loads.

Safety notice

none